

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L7	1	((("2004011584") or ("4300651")).PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2009/03/05 09:27
L8	2	((("20040011584") or ("4300651")).PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2009/03/05 09:27
L9	23	("3028924" "4068499" "4090751").PN. OR ("4300651").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/05 09:28
L10	209	((constant with velocity with joint) (CV with joint)) and (drive near3 shaft) and sprocket	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/05 09:43
L11	737	(independent adj suspension) and (double adh wishbone)	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/05 09:50
L12	245	(280/124.135).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2009/03/05 09:52
L13	14	12 and ATV	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/05 09:53
S1	9	("20030236122" "20040011584" "3218827" "4300651" "5007154" "5725453" "5951401" "6280336").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/02 14:36
S2	273	((464/140) or (464/172)).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2009/03/03 10:31
S3	42	S2 and (constant with velocity CV)	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/03 10:31
S4	231	S2 not S3	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/03 10:41
S5	209	((constant with velocity with joint) (CV with joint)) and (drive near3 shaft) and sprocket	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/03 11:38

S6	169	S5 and bearing	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/03 11:39
S7	1408	((180/371) or (180/372) or (180/373) or (180/376) or (180/380) or (180/383) or (180/384) or (180/385)). OCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2009/03/04 13:27
S8	76	S7 and (constant with velocity CV)	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/04 13:28
S9	8	("3218827").URPN.	USPAT	OR	ON	2009/03/04 13:28
S10	18	("2947158" "2981084" "2988904" "3120746" "3470712" "3857256"). PN. OR ("4112709"). URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/04 13:30
S11	6	("1838310").URPN.	USPAT	OR	ON	2009/03/04 13:35
S12	1	("1103716").URPN.	USPAT	OR	ON	2009/03/04 13:36

3/ 5/ 2009 10:47:12 AM

C:\Documents and Settings\dbrown3\My Documents\EAST\Workspaces\ 10599442 CV
joints for drive shaft movable to support driven sprocket in between case.wsp